

FELT Suitability Chart

- Suitable
- Average - contact us for guidance
- Not suitable

White/Grey Wool	Seals - Dynamic Sealing Applications	Gaskets	Bearings Packings	Cladding Thermal Insulation	Wiping Pressure Pads	Lubricating Liquid Transfer	Polishing De-burring	Filtration	Anti-vibration/Shock Sound Absorption	Medical
0.12sg	●	●	●	●	●	●	●	●	●	●
0.14sg	●	●	●	●	●	●	●	●	●	●
0.18sg	●	●	●	●	●	●	●	●	●	●
0.25sg	●	●	●	●	●	●	●	●	●	●
0.30sg	●	●	●	●	●	●	●	●	●	●
0.36sg	●	●	●	●	●	●	●	●	●	●
0.40sg	●	●	●	●	●	●	●	●	●	●
0.44sg	●	●	●	●	●	●	●	●	●	●
0.50sg	●	●	●	●	●	●	●	●	●	●
0.60sg	●	●	●	●	●	●	●	●	●	●
0.70sg	●	●	●	●	●	●	●	●	●	●
Synthetic Fibres										
250g/m ²	●	●	●	●	●	●	●	●	●	●
300g/m ²	●	●	●	●	●	●	●	●	●	●
400g/m ²	●	●	●	●	●	●	●	●	●	●
500g/m ²	●	●	●	●	●	●	●	●	●	●
750g/m ²	●	●	●	●	●	●	●	●	●	●
1000g/m ²	●	●	●	●	●	●	●	●	●	●
1250g/m ²	●	●	●	●	●	●	●	●	●	●
1500g/m ²	●	●	●	●	●	●	●	●	●	●
2000g/m ²	●	●	●	●	●	●	●	●	●	●
2500g/m ²	●	●	●	●	●	●	●	●	●	●

- Recommendations given for synthetic felts are based predominantly on Polyester fibre types.
- Suitability of other synthetic fibre types can be advised upon request.

felt in all industries